

● **Austria**

Helmut Heinz Bunzl Ges.m.b.H.
record Türautomation
Zwingenstrasse 17
A-2380 Perchtoldsdorf
Tel. + 43 1 865 88 75
Fax + 43 1 865 88 75 14
e-mail: hhb@aon.at
www.record.hhb.at

● **Denmark**

record BMT A/S
Hovedstensvej 33
DK:2650 Hvidovre
Tel. + 45 36 78 23 00
Fax + 45 36 77 16 28
e-mail: salg@recordbmt.dk
www.recordbmt.dk

● **France**

record portes automatiques SAS
ZAC-6 Rue de l'Orme Saint Germain
F-91165 Champlan Cedex
Tel. + 33 1 69 79 31 10
Fax + 33 1 69 79 31 29
e-mail: record@cordver.fr
www.record-portes-automatiques.fr

● **Germany**

record Türautomation GmbH
Dieselstrasse 70
D-42389 Wuppertal
Tel. + 49 202 60 90 10
Fax + 49 202 60 90 111
e-mail: info@tuerautomation.de
www.tuerautomation.de

● **Great Britain**

record automatic doors (UK) limited
Unit 4 D, Albany Park Industrial Estate
Frimley Road, Camberley
GB-Surrey GU 16 7 QE
Tel. + 44 1276 692 999
Fax + 44 1276 692 747
e-mail: info@record-uk.co.uk

● **Hungary**

record ajtó kft
Leshegy ut 8
H-2310 Szigetszentmiklós
Tel. + 36 24 51 53 90
Fax + 36 24 51 53 92
e-mail: recordajto@recordajto.hu

● **Netherlands**

Automatische deuren record B.V.
Cardanuslaan 30
NL-6865 HK Doorwerth
Tel. + 31 26 33 99 777
Fax + 31 26 33 99 770
e-mail: info@record-automatischedeuren.nl
www.record-automatischedeuren.nl

● **Poland**

record drzwi automatyczne Sp.zo.o
Nowa 23 Street
PL-05-500 Piaseczno, Stara Iwiczna
Tel. + 48 22 73 77 100
Fax + 48 22 737 70 08
e-mail: record@record.net.pl

● **Spain**

record puertas automaticas SA
Calle Joaquin Sorolla, n°81
E 28529 Rivas Vaciamadrid
Tel. + 34 91 499 08 80
Fax + 34 91 499 12 56
e-mail : infospain@recordpuertas.es

● **Sweden**

record dörrautomatik sweden AB
Box 19006
Wedavägen 22B
S-15225 Södertälje
Tel. + 46 8 550 646 30
Fax + 46 8 550 699 20
e-mail: info@rdarecord.se
www.rdarecord.se

● **Switzerland**

record Türautomation AG
Allmendstrasse 24
CH-8320 Fehraltorf
Tel. + 41 1 954 91 91
Fax + 41 1 954 92 00
e-mail: gch@record.ch
www.record.ch

● **USA**

KM Systems Inc.
4910 Starcrest Drive (28110)
Post Office Box 3099
Monroe, NC 28111-3099
Tel. + 1 704 289 92 12
Fax + 1 704 289 20 24
e-mail: engineering@kmsystemsinc.com
www.kmsystemsinc.com

● **International**

record international sa
Allmendstrasse 24
CH-8320 Fehraltorf
Tel. + 41 1 954 91 91
Fax + 41 1 954 92 00
e-mail: exp@record.ch



● **Production**


agtatec ltd
Allmendstrasse 24
CH-8320 Fehraltorf
Tel. + 41 1 954 91 91
Fax + 41 1 954 92 00
e-mail: agtatec@record.ch

record industry SA
Z.I. les Triboulières
F-38460 Crémieu
Tel. + 33 4 74 90 52 90
Fax + 33 4 74 90 52 91
e-mail: record.industry@cordver.fr

www.agta-record.com



your global partner for entrance solutions



Automatic sliding door

record 18 STA^{PLUS}



The beautiful solution
for modern facades record



record

your global partner for entrance solutions



Automatic sliding door record 18 STA^{PLUS} the beautiful solution

- **Elegant and feather-light in appearance**
- **Aesthetically perfect for narrow brick and column constructions**
- **Transparent door leaves move smoothly and reliably**

With a total height of 88 mm, this operator is practically invisible from the front. It fits behind the slim frame of the glazed façade, and even the top profile is integrated into the operator housing. This allows the space created by the glass to remain uncluttered.

Despite its slim lines, the operator also uses system 16 rollers, ensuring whisper-quiet, dependable operation. The automatic sliding door record 18 STA^{PLUS} uses system 16's proven drive electronics.





Technical Data

Clear opening width A	
Biparting sliding door	850 - 2,000 mm
Single sliding door	850 - 2,000 mm
Clear height of passage G	
Recommended maximum height	2,500 mm
Maximum weight of door leaves	
Biparting sliding door	2 x 100 kg
Single sliding door	1 x 150 kg
Operator dimensions, incl. housing	
Height	88 mm
Depth	175 mm
Door movements*	
Biparting sliding door	0.7 m in 1.0 sec.
Single sliding door	0.7 m in 1.5 sec.
Electrical connection data	
Mains voltage	230 V, 50/60 Hz
Rated power	0,6 A
Rated capacity	100 W
Rated capacity standby mode (door shut)	14 W
Fuse protection	min. 2,5 A slow

if door leaf weight equals 75% of permissible max. weight

